产品认证证书

太阳能产品认证

证书编号：CQC21024319039

发证日期：2021 年 11 月 09 日

有效期至：长期有效

委托人名称及注册地址	杭州禾迈电力电子股份有限公司 浙江省杭州市拱墅区康景路 18 号 11 幢三楼
制造商名称及注册地址	杭州禾迈电力电子股份有限公司 浙江省杭州市拱墅区康景路 18 号 11 幢三楼
生产企业名称及生产地址	杭州禾迈电力电子股份有限公司 浙江省杭州市拱墅区康景路 18 号 11 幢三楼
产品名称和系列、规格、型号	微型逆变器 HMT-2250-6T，HMT-1800-6T（见附件）
产品标准和技术要求	NB/T32004-2018
认证模式	产品型式试验+初次工厂检查+获证后监督

上述产品符合 CQC33-461239-2018 认证规则的要求，特发此证。

本证书的有效性依据发证机构的定期监督获得保持。

可通过扫描下方二维码或登录国家认监委网站（www.cnca.gov.cn）查验证书信息

签发：谢肇煦

中国质量认证中心

CHINA QUALITY CERTIFICATION CENTRE 中国质量认证中心

T 0016143

CERTIFICATE OF PRODUCT CERTIFICATION

SOLAR PRODUCT CERTIFICATE

CERTIFICATE NO.: CQC21024319039

Valid from: Nov.09,2021

Valid until:long-term

NAME AND REGISTERED ADDRESS OF THE APPLICANT	Hoymiles Power Electronics Inc. 3rd Floor, 11th Building, No.18. Kangjing Road, Gongshu District, Hangzhou, Zhejiang
NAME AND REGISTERED ADDRESS OF THE MANUFACTURER	Hoymiles Power Electronics Inc. 3rd Floor, 11th Building, No.18. Kangjing Road, Gongshu District, Hangzhou, Zhejiang
NAME AND LOCATION OF THE FACTORY	Hoymiles Power Electronics Inc. 3rd Floor, 11th Building, No.18. Kangjing Road, Gongshu District, Hangzhou, Zhejiang
PRODUCT NAME, MODEL AND SPECIFICATION	PV Microinverter HMT-2250-6T , HMT-1800-6T (See Appendix)
THE STANDARDS AND TECHNICAL REQUIREMENTS FOR THE PRODUCTS	NB/T32004-2018
TYPE OF CERTIFICATION SCHEMES	Type Testing of Product + Initial Factory Inspection + Follow up Factory Inspection

This is to certify that the above mentioned product(s) complies with the requirements of certification rules of CQC33-461239-2018.

The validity of the certificate is subject to positive result of the regular follow up inspection by issuing certification body.

The certificate information is available through the QR code below or CNCA's website: www.cnca.gov.cn

SIGNATURE: 谢肇煦

CHINA QUALITY CERTIFICATION CENTRE

中国质量认证中心

T 0016143

产品认证证书

太阳能产品认证

附　　录　　第 1 页 共 1 页

证书编号：CQC21024319039　　纸　号：16143

HMT-2250-6T

直流输入:MPPT 电压范围 16V-48Vdc,最大直流输入电压 60Vdc,最大输入电流 11.5A*6;
交流输出:3/N/PE～,230V/400V,50Hz,3.26A*3,额定交流输出功率 2.25kW;

HMT-1800-6T

直流输入:MPPT 电压范围 16V-48Vdc,最大直流输入电压 60Vdc,最大输入电流 11.5A*6;
交流输出:3/N/PE～,230V/400V,50Hz,2.61A*3,额定交流输出功率 1.80kW.

注：此附录与证书同时使用时有效。

中国质量认证中心