




Microinverter Datasheet

HMS-800-2T
HMS-900-2T
HMS-1000-2T

Description

The Hoymiles HMS-1000-2T series microinverters are designed for high-powered solar panels and are among the top-performing 2-in-1 microinverters on the market.

Each microinverter can connect up to 2 panels, with independent MPPT and monitoring maximizing the power production of your installation.

The new Sub-1G wireless solution enables more stable communication with Hoymiles gateway DTU.

Features

01

High-powered microinverter for 2-in-1 with output power up to 1000 VA

02

With Reactive Power Control, compliant with EN 50549-1:2019, VDE-AR-N 4105:2018, UL 1741, ABNT NBR 16150, etc.

03

Safer for rooftop solar stations with rapid shutdown compliance and isolated transformer

04

Independent MPPT and monitoring ensure greater energy harvest and easier maintenance

05

2-in-1 design enables faster installation

06

Sub-1G wireless solution allows stable communication in commercial and industrial settings

Technical Specifications

Model	HMS-800-2T				HMS-900-2T				HMS-1000-2T			
Input Data (DC)												
Commonly used module power (W)	320 to 540+				360 to 600+				400 to 670+			
Maximum input voltage (V)					65							
MPPT voltage range (V)					16 - 60							
Start-up voltage (V)					22							
Maximum input current (A)	2 × 14				2 × 15				2 × 16			
Maximum input short circuit current (A)					2 × 25							
Number of MPPTs					2							
Number of inputs per MPPT					1							
Output Data (AC)												
Maximum continuous output power (VA)	800				900				1000			
Maximum continuous output current (A)	3.85	3.64	3.48	3.33	4.33	4.09	3.91	3.75	4.81	4.55	4.35	4.17
Nominal output voltage	208	220	230	240	208	220	230	240	208	220	230	240
Nominal output range (V)*					180 - 275							
Nominal frequency/range (Hz)*					50/45 - 55 or 60/55 - 65							
Adjustable power factor (@ nominal power)					> 0.99 default 0.8 leading ... 0.8 lagging							
Total harmonic distortion (@ nominal power)					< 3 %							
Maximum units per 10 AWG branch**	8	8	9	9	7	7	8	8	6	7	7	7
Maximum units per 12 AWG branch**	5	5	5	6	4	4	5	5	4	4	4	4
Efficiency												
Peak efficiency	96.70%				96.50%				96.50%			
Nominal MPPT efficiency					99.80%							
Night power consumption (mW)					< 50							
Mechanical Data												
Ambient temperature range (°F)					-40 to 149 (-40°C to +65°C)							
Dimensions (W × H × D [inches])					10.28 × 7.09 × 1.38 (261 × 180 × 35.1 mm)							
Weight (lbs)					7.06 (3.2 kg)							
Enclosure rating					Outdoor-IP67 (NEMA 6)							
Cooling					Natural convection-No fans							
Features												
Communication					Sub-1G							
Type of isolation					Galvanically Isolated HF Transformer							
Monitoring					S-Miles Cloud (Hoymiles Monitoring Platform)							
Compliance					UL 1741, ABNT NBR 16150:2013, ABNT NBR 16149:2013							
* : Nominal voltage/frequency range can vary depending on local requirements.												
** : Refer to local requirements for the exact number of microinverters per branch.												